

# RQD / HVAC-R EXTERNAL SEALING CONNECTION TOOL

External sealing connection tool for attachment to Hansen® and PCU® tips under pressure.

## CONNECTS TO:

Hansen® Tips PCU® Tips



## SPECIFICATIONS

Pressure Rating	Operating Temperatures	Materials of Construction
Vacuum to 750 psi (52 bar)	-40°F to +250°F (-40°C to +121°C)	Black Oxide Steel
Termination Port		Seal Material*
1/4 or 3/8 NPT		Neoprene®

\* Additional seal material types available, consult factory.

- i Designed for ISO 7241-1 Series B coupling "Tips"
- i RQD can mate with, but not limited to, the following brands: Parker® 60, PCU® 250 & 410, Hansen® HK, SABE® IB Series (China), AeroQuip® FD45, Faster® HNV Series, Snap-Tite® 72 series, Stucchi® IRB, Perfecting® H Series, Safeway® S10 Series, Tomco® H Series, Cejn® X75, Foste®r HX-S, and Nitto® 250.

## ACTUATION METHOD

**Sleeve / Lever Handle:** Easy sleeve connection is ergonomic and eliminates repetitive twisting and turning, cam over lever handle opens poppets under pressure

## ICON™ TECHNOLOGY

Consult Factory

## ACCESSORIES

Visit [fastestinc.com](http://fastestinc.com)

- 1 Sleeve lock connection prior to pressure engagement minimizes force to connect through handle activation
- 2 Connects and vents even under pressure using lever handle to keep refrigerant away from the operator
- 3 Internal HTPE seal to keep refrigerant from exhaling back onto operator
- 4 Internal poppet style seal for dry refrigerant operation
- 5 Minimal maintenance required

# RQD / HVAC-R EXTERNAL SEALING CONNECTION TOOL



Ordering Information				Dimensions			
Connects To	Part Number	Replacement Seals Bulk Pack (5)	Rebuild Kit	A	B	C	D

**RQD** | Lever Action Style for PCU\* Tips

1/4 PCU*— Model 64 Tip	KA04PA	KSA04	KR04A	1.75 (44.5)	4.39 (111.5)	7.00 (177.8)	1/4 NPT
1/4 PCU*— Model 61 Tip	KA04PB	KSM04	KR04				3/8 NPT
3/8 PCU*— Model 78 Tip	KA06PA	KSM06PB	KR06PA	1.95 (49.5)	4.54 (115.3)	7.00 (177.8)	3/8 NPT
3/8 PCU*— Model 66 Tip	KA06PB	KSM06PB	KR06PB				

**RQD** | Lever Action Style for Hansen\* Tips

1/4 Hansen* 2K	KA04HB	KSM04	KR04	1.75 (44.5)	4.39 (111.5)	7.00 (177.8)	1/4 NPT
3/8 Hansen* 3K	KA06HB	KSM06HB	KR06HB	1.95 (49.5)	4.54 (115.3)		3/8 NPT

Dimensions: inch (mm)



**DON'T SEE A SOLUTION FOR YOUR APPLICATION?** Submit a custom application form and drawing to [fastsales@fastestinc.com](mailto:fastsales@fastestinc.com) or to your local distributor.